

Cellular Gateway
Accessories

ACC-POE-90W-E
Outdoor 90W PoE++ Injector

IP67-rated PoE++ injector for powering the GC31-E in harsh environments.
The GC31-E can be mounted directly on the injector.



Tech Specs

Model Number	ACC-POE-90W-E	Weight	2.9kg / 6.4lbs
Input	100-240VAC 2.0A 50-60Hz Use the included AC power cord (region-specific) or connect directly to conduit, junction box, or AC power tap.	Dimensions	Length: 247mm / 9.7in Width: 170mm / 6.7in Height: 74mm / 2.9in
Output	Single port RJ45 PoE IEEE 802.3bt Type 4 90W Gigabit compatible	Mounting Options	Wall or pole mounting (mount plate and pole straps included)
Operating Temperature	-40°C to 50°C / -40°F to 122°F IP67 rated		



ACC-POE-90W

Indoor 90W PoE++ Injector

PoE++ injector for powering the GC31-E. Use the injector indoors or within a NEMA enclosure.



Tech Specs

Model Number	ACC-POE-90W	Weight	0.5kg / 1.1lbs
Input	100-240VAC 2.5A 50-60Hz AC power cord included (region-specific)	Dimensions	Length: 166mm / 6.5in Width: 80mm / 3.1in Height: 44mm / 1.7in
Output	Single port RJ45 PoE IEEE 802.3bt Type 4 90W Gigabit compatible	Mounting Options	Wall mounting (built-in screw tabs)
Operating Temperature	-20°C to 40°C / -4°F to 104°F		



ACC-ADAP-54V

AC/DC Power Adapter

Barrel jack AC/DC power adapter included with the GC31. If purchased to power the GC31-E, place the adapter indoors or within a NEMA enclosure.



Tech Specs

Model Number	ACC-ADAP-54V	Weight	0.5kg / 1.0lbs
Input	100-240VAC 15A Max 50-60Hz AC power cord included (region-specific)	Dimensions	Length: 134mm / 5.3in Width: 60mm / 2.4in Height: 31mm / 1.2in
Output	54V = 1.48A, 79.9W		



ACCX-TAP-DC100-E

AC/DC 7-Pin Light Pole Power Tap

Power the GC31-E by tapping into the electrical circuit of a streetlight. The 7-pin power tap connects directly to AC and provides DC via PoE.



Tech Specs

Model Number	ACCX-TAP-DC100-E	Weight	0.5kg / 1lbs
Input	105-240VAC, single phase Optional pass-through photocontrol port	Dimensions	Height: 135mm / 5.3in Diameter: 114mm / 4.5in
Output	Single port RJ45 PoE 100W, 48VDC	Mounting Options	ANSI C136.10 compliant twist-to-lock plug
Operating Temperature Range	-30°C to 50°C / -22°F to 122°F		



Ordering Information

Cellular Gateway accessories pricing

Model Number	Description	Cost (MSRP) USD
ACC-ADAP-54V-AU	AC/DC Barrel Jack Power Adapter, 54V, Indoor, Australia Type I Plug	\$89
ACC-ADAP-54V-EU	AC/DC Barrel Jack Power Adapter, 54V, Indoor, Europe Type F Plug	\$89
ACC-ADAP-54V-NA	AC/DC Barrel Jack Power Adapter, 54V, Indoor, North America Type B Plug	\$89
ACC-ADAP-54V-UK	AC/DC Barrel Jack Power Adapter, 54V, Indoor, United Kingdom Type G Plug	\$89
ACC-POE-90W-AU	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, Australia Type I Plug	\$169
ACC-POE-90W-EU	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, Europe Type F Plug	\$169
ACC-POE-90W-NA	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, North America Type B Plug	\$169
ACC-POE-90W-UK	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, United Kingdom Type G Plug	\$169
ACC-POE-90W-E-AU	90W PoE++ (802.3bt Type 4) Injector, GigE, Outdoor, Australia Type I Plug	\$299
ACC-POE-90W-E-EU	90W PoE++ (802.3bt Type 4) Injector, GigE, Outdoor, Europe Type F Plug	\$299
ACC-POE-90W-E-NA	90W PoE++ (802.3bt Type 4) Injector, GigE, Outdoor, North America Type B Plug	\$299
ACC-POE-90W-E-UK	90W PoE++ (802.3bt Type 4) Injector, GigE, Outdoor, United Kingdom Type G Plug	\$299
ACCX-TAP-DC100-E	FP AC/DC 7-Pin Power Tap, 100W PoE Output, Outdoor, Model Number: FP287A-180-BEN-A	\$399