



CD51 Indoor/Outdoor Dome Tech Specs

Sensor Resolution	5MP (2688 x 1944)	Focal Length	f=2.8–8mm
Lens Type	3x Optical Zoom	Iris	P-Iris
Image Sensor	1/2.8" Progressive CMOS	Aperture	F1.3–F2.4
IR Range	30m / 98ft in low light	Resistance Rating	Rating IK08, FCC, IEC60950-1
Field of View	Horizontal: 38° to 105° Vertical: 29° to 77° Diagonal: 48° to 126°	Operating Specs	Power: 11W (IEEE 802.3af PoE) Temperature: -10°C–50°C (14°F–122°F) Humidity: 90%
Dimensions	With mount plate: Ø: 146mm / 5.75in, H: 104.3mm / 4.11in ; 736g / 25.96oz Without mount plate: Ø: 146mm / 5.75in, H: 99.8mm / 3.93in ; 593g / 20.92oz	Connectivity	Ethernet: 10/100Mbps RJ-45 cable connector for Network/PoE connection
		RTSP	RTSP 1.0 RFC 2326 Max Concurrent Streams: 2 Audio Support: Yes

SKU	Max Days of Retention	Onboard Storage
CD51-30-HW	30	128GB
CD51-30E-HW	30	128GB
CD51-60-HW	60	256GB
CD51-60E-HW	60	256GB
CD51-90-HW	90	384GB
CD51-90E-HW	90	384GB
CD51-120-HW	120	512GB
CD51-120E-HW	120	512GB
CD51-365-HW	365	2TB
CD51-365E-HW	365	2TB