



CD61 Indoor/Outdoor Dome Tech Specs

Sensor Resolution	4K (3840 x 2160)	Focal Length	f=2.8-8mm
Lens Type	Fixed 3x Optical Zoom	Iris	P-Iris
Image Sensor	1/2.8" Progressive CMOS	Aperture	F1.3-F2.4
IR Range	30m / 98ft in low light	Resistance Rating	Rating IK08, FCC, IEC60950-1
Field of View	Horizontal: 41° to 116° (92°) Vertical: 23° to 62° (53°) Diagonal: 47° to 136° (103°)	Operating Specs	Power: 11W (IEEE 802.3af PoE) Temperature: -10°C - 50°C (14°F - 122°F) Humidity: 90%
Dimensions	With mount plate: Ø: 146mm / 5.75in, H: 104.3mm / 4.11in; 736g / 25.96oz Without mount plate: Ø: 146mm / 5.75in, H: 99.8mm / 3.93in; 593g / 20.92oz	Connectivity	Ethernet: 10/100Mbps RJ-45 cable connector for Network/PoE connection

SKU	Max Days of Retention	Onboard Storage
CD61-30-HW	30	384GB
CD61-30E-HW	30	384GB
CD61-60-HW	60	1TB
CD61-60E-HW	60	1TB
CD61-90-HW	90	2TB
CD61-90E-HW	90	2TB