

CP52-E-F Government-Grade PTZ Camera

5MP PTZ for Expansive and Detailed Coverage of Large Government Areas



Overview

The CP52-E-F government-grade PTZ camera features a 1 / 2.8" progressive CMOS image sensor, varifocal lens with 28x motorized optical zoom, and 100 meters / 328 feet of IR range for reliable 5MP image quality at distance in inclement weather. The CP52-E-F also includes FIPS 140-validated encryption and is both TAA and FY2019 NDAA compliant – essential compliance criteria for government-grade deployments. The CP52-E-F is compatible with the standard Verkada Command platform, as well as Command for GovCloud, Verkada’s FedRAMP® Moderate Authorized environment.

To complement its [sentry mode](#), organizations can pair the CP52-E-F with up to three context cameras for precise and automated monitoring of individuals across an expansive field of view. With its onboard CV22S Ambarella processor delivering advanced analytics like AI-powered search and person of interest (POI) alerts, the CP52-E-F offers privacy-sensitive monitoring of large areas such as parking lots and courtyards.

Engineered in-house, the CP52-E-F has a turret design that enhances its range of motion, and effectively reduces blind spots. Advanced motor mechanisms allow for quick and seamless transitions between positions with ultra low latency (<500 milliseconds). The CP52-E-F features a robust metal housing, IP66 weather rating, and IK10 impact rating to help ensure functionality in harsh conditions and inclement weather.

Key features

Excellent image quality

- 1 / 2.8" progressive CMOS image sensor
- 5MP resolution
- Varifocal lens with 28x optical zoom
- 100 meters / 328 feet of IR range for long-range nighttime viewing

Advanced analytics

- Onboard CV22S Ambarella processor enables people and vehicle analytics
- Person of interest (POI) alerts for proactive monitoring

Durability and weather protection

- Robust metal housing
- IP66 weather rating and IK10 impact rating
- Operability between -40°C to 50°C / -40°F to 122°F

Hybrid cloud architecture

- Onboard storage and processing helps reduce bandwidth consumption, enabling coverage at scale
- 30 - 180 days (512GB - 3TB) of onboard storage
- Redundant cloud backup and unlimited cloud-based archiving of footage

Automated monitoring

- Sentry mode with up to three context cameras for automated monitoring of vast areas

Government-Grade Security

- Meets the FIPS 140 standard, as validated by NIST
- FedRAMP Ready status at the Moderate impact level as designated by the Federal Risk and Authorization Management Program
- TAA and FY2019 NDAA compliant



CP52-E-F Tech specs

Camera features

Image Sensor	1/2.8" Progressive CMOS	Shutter Speed	1/30 sec. to 1/10,000 sec.
Sensor Resolution¹	5MP (2688 x 1944)	Day/Night	IR-cut filter for day and night function
Lens Type	Varifocal; motorized zoom	IR Cut Filter	Yes
Focal Length	5.2mm – 148.15mm	IR Range	100m / 328ft
Aperture	F1.3 – F4.8	Minimum Illumination	0.8 lux @ F1.4 (Color) 0 lux @ F1.4 with IR Illuminators on
Iris	DC Iris	Onboard Storage	Capacity: From 512GB to 3TB Card: MicroSD, SDXC
Field of View	Horizontal: 55°–2° Vertical: 42°–1.5° Diagonal: 66°–2.5°	CPU	Ambarella CV22S66
Sensor Movement	Tilt: 220° Pan: 360°		

Standard video settings

Compression	H.265 (historical video only), H.264	Historical Video Settings	Adaptive quality ¹
Frame Rate²	24fps	WDR Technology	True WDR, dual exposure
Live Streaming Settings³	Static: 1,000 Kbps (SQ), 3,000 Kbps (HQ) Moving: 2,000 Kbps (SQ), 4,500 Kbps (HQ)		

Standard audio settings

Audio	Not supported
--------------	---------------

Power and network

Power Input⁴	With IR: IEEE 802.3bt Type 3 PoE++ Without IR: IEEE 802.3at Type 2 PoE+ Extended temperature range: IEEE 802.3bt Type 3 PoE++	Connectivity	RJ-45 cable connector for network/PoE connection; 10 / 100 / 1000 Mbps
Power Consumption⁴	With IR: 43-57V, 1.00-0.74A, 42.3W Without IR: 43-57V, 0.55-0.41A, 23.3W Extended temperature range: 43-57V, 1.04-0.77A, 44.0W	RTSP	RTSP 1.0 RFC 2326 Max concurrent streams: 2 Audio support: No

1. All our cameras record in "adaptive quality," capturing both standard (SQ) and high quality (HQ) streams. SQ video is stored up to the amount of retention specified by the customer. The amount of HQ video stored on the camera will depend on the amount of motion detected by the camera over time. To learn more, visit our website:

<https://docs.verkada.com/docs/adaptive-quality-recording-whitepaper.pdf>

2. Frame rate can be adjusted by support.

3. The listed ranges represent the uplink bandwidth based on target bitrates. To learn more, visit Verkada's Knowledge Base and read "Understanding Variable Bitrates for Verkada PTZ Cameras".

4. Extended temperature range includes operating temperatures below -10°C / 14°F and assumes IR will be enabled.



CP52-E-F Tech specs

General

Operating Temperature	-40°C to 50°C / -40°F to 122°F	LED Indicator	System power and status indicator
Humidity	0 to 90%	Warranty	5 Years
Certifications	FCC, IC, UL, CB, CE, UKCA, Japan VCCI, AS/NZS (RCM), IK10 impact rating, IP66 weather rating	Included Accessories	Rubber cap, pendant cap, T30 security L-wrench

Mechanical

Weight	Camera: 7.07kg / 15.6lbs Pendant cap: 0.41kg / 0.9lbs	Body	Aluminum, plastic
Dimensions	Ø: 256.0mm / 10.08in, H: 406.0mm / 15.98in with pendant cap Ø: 256.0mm / 10.08in, H: 336.0mm / 13.23in without pendant cap		

Dimensions

256.0mm / 10.08in



406.0mm / 15.98in

Software capabilities

Alerts	Camera status, motion detection, people detection, vehicle detection, person of interest detection, crowd detection	Streaming and Storage	Cloud backup, configurable retention days, selectable storage location, timelapse, RTSP
People Analytics	People search, attribute search, face search, sentry mode, motion search, trajectory analysis, selective face blurring	Sharing and Privacy	Live links, audit log
Vehicle Analytics	Vehicle search, attribute search, motion search, trajectory analysis	Controllers⁵	Mouse, keyboard, Xbox Wireless Controller, joystick

Coverage examples



360° pan



220° tilt

5. For details on the supported controllers for PTZ cameras, refer to the article [here](#).



Ordering information

CP52-E-F pricing

Model number	MP ¹	WDR	Lens	IR range	Onboard storage	Maximum SQ onboard retention ¹	People/vehicle analytics	US cost (MSRP) ^{USD}	WW cost (MSRP) ^{USD}
CP52-512E-HW-F	5MP	✓	Zoom	100m / 328ft	512GB	30 Days	✓	\$4,999	\$4,799
CP52-1TBE-HW-F	5MP	✓	Zoom	100m / 328ft	1TB	60 Days	✓	\$6,399	\$6,199
CP52-1P5TBE-HW-F	5MP	✓	Zoom	100m / 328ft	1.5TB	90 Days	✓	\$7,799	\$7,599
CP52-3TBE-HW-F	5MP	✓	Zoom	100m / 328ft	3TB	180 Days	✓	\$10,799	\$10,599



Ordering information

Video Security Cloud License Pricing (new/capacity increase)

Model number	Description	US cost (MSRP) ^{USD}	WW cost(MSRP) ^{USD}
LIC-CAM-1Y-CAP	1-year camera license, capacity increase	\$249	\$249
LIC-CAM-3Y-CAP	3-year camera license, capacity increase	\$659	\$659
LIC-CAM-5Y-CAP	5-year camera license, capacity increase	\$1,099	\$1,099
LIC-CAM-10Y-CAP	10-year camera license, capacity increase	\$2,199	\$2,199
LIC-CAM-1Y-CAP-G	1-Year Camera License for Government, Capacity Increase	\$299	\$299
LIC-CAM-3Y-CAP-G	3-Year Camera License for Government, Capacity Increase	\$809	\$809
LIC-CAM-5Y-CAP-G	5-Year Camera License for Government, Capacity Increase	\$1,349	\$1,349
LIC-CAM-10Y-CAP-G	10-Year Camera License for Government, Capacity Increase	\$2,699	\$2,699

Video Security Cloud License Pricing (renewal)

Model number	Description	US cost (MSRP) ^{USD}	WW cost(MSRP) ^{USD}
LIC-CAM-1Y-RNW	1-year camera license, renewal	\$249	\$249
LIC-CAM-3Y-RNW	3-year camera license, renewal	\$659	\$659
LIC-CAM-5Y-RNW	5-year camera license, renewal	\$1,099	\$1,099
LIC-CAM-10Y-RNW	10-year camera license, renewal	\$2,199	\$2,199
LIC-CAM-1Y-RNW-G	1-Year Camera License for Government, Renewal	\$299	\$299
LIC-CAM-3Y-RNW-G	3-Year Camera License for Government, Renewal	\$809	\$809
LIC-CAM-5Y-RNW-G	5-Year Camera License for Government, Renewal	\$1,349	\$1,349
LIC-CAM-10Y-RNW-G	10-Year Camera License for Government, Renewal	\$2,699	\$2,699



Accessories

Recommended accessories

Model Number	Description
ACC-MNT-CORNER-1	Corner Mount
ACC-MNT-POLE-1	Pole Mount
ACC-MNT-XLARM-1	Large Arm Mount
ACC-POE-90W-AU	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, Australia Type I Plug
ACC-POE-90W-EU	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, Europe Type F Plug
ACC-POE-90W-NA	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, North America Type B Plug
ACC-POE-90W-UK	90W PoE++ (802.3bt Type 4) Injector, GigE, Indoor, United Kingdom Type G Plug