



1/2.8" Progressive CMOS Sensor  
 Built-in IR Illuminators  
 P-iris Lens"

<b>Image Sensor</b>	1/2.8" Progressive CMOS	<b>LED Indicator</b>	System power and status indicator
<b>Maximum Resolution</b>	2048x1536 (3MP)	<b>Connectors</b>	RJ-45 cable connector for Network/PoE connection
<b>Lens Type</b>	Vertical	<b>Power Input</b>	IEEE 802.3af PoE
<b>Focus</b>	Auto focus	<b>Power Consumption</b>	11 W
<b>Focal Length</b>	f = 3 ~ 9 mm	<b>Dimensions</b>	Ø 145 mm x 106 mm / 5.7 in x 4.2 in
<b>Aperture</b>	F1.2 ~ F2.3	<b>Weight</b>	503g / 1.1lb
<b>Auto-iris</b>	P-iris	<b>Certifications</b>	IK08 vandal resistance FCC, ICES, IEC60950-1
<b>Field of View</b>	41° ~ 86° Horizontal 31° ~ 64° Vertical 51° ~ 113° Diagonal	<b>Operating Temperature</b>	-10°C ~ 50°C (14°F ~ 122°F)
<b>Shutter Time</b>	1/5 sec. to 1/16000 sec.	<b>Humidity</b>	90%
<b>Day/Night</b>	IR-cut filter for day & night function	<b>Included Accessories</b>	Setup guide, T10 security Torx screwdriver, screw pack, mounting template
<b>IR Illuminators</b>	30 meters in low light conditions	<b>Ordering Information</b>	D30-HW: Verkada Indoor Dome Camera